

Weather proof side opening Polycarbonate box camera housing with IP66 standard



- IP66
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower (optional)
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in Polycarbonate

## Specification

Model	CSAH135	CSAH135-H	CSAH135-HB
Type	Outdoor side open camera housing	Outdoor side open camera housing	Outdoor side open camera housing
Weatherproof	IP66	IP66	IP66
Material/Color	Polycarbonate/Beige	Polycarbonate/Beige	Polycarbonate/Beige
Power		DC 12V/AC 24V/AC 110V/AC 220V	DC 12V/AC 24V/AC 110V/AC 220V
Appearance Size (W × H × L)	151 × 145 × 390 mm	151 × 145 × 390 mm	151 × 145 × 390 mm
View Area (Diameter)	74 mm	74 mm	74 mm
Suitable Camera Size (W × H × L)	95 × 80 × 250 mm	95 × 80 × 250 mm	95 × 80 × 250 mm
Heater Control	-	Heater: on: 15 °C; off: 25 °C	Heater: on: 15 °C; off: 25 °C
Blower Control	-	-	Blower: on: 35 °C, off: 25 °C
Environmental Operation Temperature	-	-10 ~ 50 °C	-10 ~ 50 °C
Temper Glass Thickness	2 mm	2 mm	2 mm
Bracket	Die casting cable management bracket	Die casting cable management bracket	Die casting cable management bracket
Packing	8 pieces in one carton	8 pieces in one carton	8 pieces in one carton
Unit N.W, G.W.	2.06 Kg, 2.56 Kg	2.06 Kg, 2.56 Kg	2.06 Kg, 2.56 Kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-	-
IR Distance	-	-	-
IR H.V. Angle	-	-	-
IR LEDs	-	-	-
Expected Lifetime	-	-	-
IR Light On/Off	-	-	-

\*Design and specifications are subject to change without prior notice.