

PoE weather proof side opening Polycarbonate box camera housing with IP66 standard



- ❑ DC 12V/1.667 A PoE power support
- ❑ Support high-power input and output power up to 20 W
- ❑ For PoE and non-PoE cameras
- ❑ Build in heater/blower (optional)
- ❑ Adjustable sliding camera tray & sealed cable entry glands
- ❑ Fully-cable management system with swivel bracket
- ❑ Made in Polycarbonate

## Specification

Model	CSAH135P	CSAH135P-H	CSAH135P-HB
Type	Outdoor Side Open Camera Housing	Outdoor Side Open Camera Housing	Outdoor Side Open Camera Housing
Weatherproof	IP66	IP66	IP66
Material/Color	Polycarbonate/Beige	Polycarbonate/Beige	Polycarbonate/Beige
DC Output Power	DC 12 V/1.667 A	DC 12 V/1.667 A	DC 12 V/1.667 A
LAN Interface	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)
Appearance Size (W × H × L)	151 × 145 × 390 mm	151 × 145 × 390 mm	151 × 145 × 390 mm
View Area (Diameter)	74 mm	74 mm	74 mm
Suitable Camera Size (W × H × L)	95 × 80 × 250 mm	95 × 80 × 250 mm	95 × 80 × 250 mm
Heater Control	-	Heater: on: 15 °C; off: 25 °C	Heater: on: 15 °C; off: 25 °C
Blower Control	-	-	Blower: on: 35 °C, off: 25 °C
Environmental Operation Temperature	-10 ~ 50 °C	-10 ~ 50 °C	-10 ~ 50 °C
Temper Glass Thickness	2 mm	2 mm	2 mm
Bracket	Die casting cable management bracket	Die casting cable management bracket	Die casting cable management bracket
Packing	8 pieces in one carton	8 pieces in one carton	8 pieces in one carton
Unit N.W, G.W.	2.06 Kg, 2.56 Kg	2.06 Kg, 2.56 Kg	2.06 Kg, 2.56 Kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-	-
IR Distance	-	-	-
IR H.V. Angle	-	-	-
IR LEDs	-	-	-
Expected Lifetime	-	-	-
IR Light On/Off	-	-	-

\*Design and specifications are subject to change without prior notice.