

540 TV lines, f = 4.3 mm fixe lens, digital Day/Night, 25 m IR, indoor bullet camera



- 1/3" CCD
- Lens: f = 4.3 mm, F1.6
- High resolution: 540 (Day/Night) TV lines
- Min illumination: 0.06 lx (25 %, F1.6, AGC super), IR on: 0 lx
- IR distance: 25 m

Specification

Signal system	NTSC	PAL
Camera		
Image device	1/3" CCD	
Effective pixels (H x V)	811 x 507	795 x 595
Scanning system	2:1 Interlace	2:1 Interlace
Scanning frequency	V: 59.94 Hz, H: 15.734 kHz	V: 50 Hz, H: 15.625 kHz
Sync system	Internal	
Horizontal resolution	540 TV lines (Day/Night mode)	
Video output	1 Vpp composite output, 75 ohm	
S/N ratio	50 dB (AGC off)	
Minimum illumination	0.06 lx (25 %, F1.6, AGC super); 0.3 lx (50 %, F1.6, AGC high); 0 lx IR on (IR LED 25 m)	
Iris control	A.E.S.	
White balance	ATW/AWB switchable (3,200 ~ 10,000 K)	
Wide dynamic range function	52 dB	
BLC	On/Off	
Gamma correction	0.45	
Gain control	AGC	
Electric shutter	Auto 1/60 to 1/120,000 sec	Auto 1/50 to 1/120,000 sec
Flickerless	-	
Day/Night	Digital	
DNR	-	
OSD	-	
Slow shutter	-	
Privacy znoe	-	
Remote protocole	-	
Lens		
Lens mount	-	
Focal length	f = 4.3 mm/F1.6	
General		
Power requirement	DC 12 V	
Power consumption	4.5 W (max.)	
Operating temperature	-10 °C ~ 50 °C	
Operating humidity	30 % ~ 90 % RH (max.), IP66	
Storage temperature	-20 °C ~ 60 °C	
Dimensions (D x H)	57 mm x 68 mm	
Weight	250 g approx.	
Ordering information	CSB111N12	CSB111P12

Bullet
Color
1/3"
CCD

540
TV lines

Digital
Day/Night

IP66
25 m
IR LED