

16 ch, 2.5" SATA HDD compatible up to 250 GB



- 16 channel
- Selectable video quality: VGA (640 x 480); HVGA (640 x 240)
- Programmable recording rate: 5 ~ 25/30 fps (PAL/NTSC)
- MPEG4 compression
- Removable hard disk
- Low power consumption: max. 12 W
- Vibration test: 2.5 G (5 ~ 500 Hz; random)

## Specification

Signal system	NTSC	PAL
Video input	16 BNC	
Video output	1 BNC	
Recording frame	30 fps	25 fps
Video quality	1 ch: 640 x 480 4 ch: 320 x 240	
Resolution	640 x 480	
Audio input	2 BNC	
Audio output	1 BNC	
Recording mode	continue / interval / scheduled / event	
Playback speed	FF/RW x1, x2, x4, x8, x16	
Search mode	date / time / event / alarm recording	
Pre / post recording	10 ~ 600 s	
Storage	2.5" SATA HDD (up to 250 GB) CF card (up to 8 GB)	
Digital in/output	6 alarm in / 2 alarm out	
USB port	1 USB 2.0	
Control port	1 RS485	
Network port	ethernet 10/100M RJ45	
Serial port	2 RS232	
Power supply	10 ~ 30 W	
Power consumption	12 W max.	
Operation temperature	-10 ~ 70 °C (CF card) 5 ~ 55 °C (with HDD; no cooling fan)	
Anti-vibration	2.5 Grms (5 ~ 500 Hz; random)	
Operation mode	OSD menu (on screen display)	
Video display	real time	
Dimensions (L x W x H)	274 mm x 160 mm x 55 mm	
Net Weight	2.3 kg	
<b>PC software</b>		
playback software	Quick Time 6.5 or 7.2 E-Player	
<b>Certification</b>		
Anti-vibration	Ref#: 320-94508-083	
CE	NEI-EMC-1-0612096	
FCC	NEI-FCCE-1-0612096	

DVR  
Mobile

MPEG4

2.5"  
SATA HDD

16 ch

† Product specifications and features are subject to change without prior notification.