

IP vandal camera, 1.3 Megapixel CMOS, H.264/MPEG4/JPEG, f = 2.7 ~ 9 mm vari-focal lens, 2-way audio, IP66



- 1.3 Megapixel resolution at 15 fps
- H.264/MPEG-4/JPEG dual streams simultaneously
- Vandal proof & IP66
- Varifocal auto iris lens
- 2-way audio
- Mobile view support
- PoE support

Specification

	Model Name	ISM3121E
Video	Network Compression	Triple Streams: H.264/MPEG-4/JPEG
	Pixels (H x V)	1.3 Megapixel, D1, 4CIF, CIF, QCIF
	Max. Frame Rate	Max. 15 fps
	Video Profile	11 profiles simultaneously H.264: SXGA, VGA, QVGA, QVGA MPEG4: VGA, QVGA, QVGA MJPEG: SXGA, VGA, QVGA, QVGA
	Safety	User-ID and password
	Protocol	TCP, UDP, HTTP, FTP, SMTP, NTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP, RTP, 3GPP, ICMP, SAMBA
	Number of User	20 simultaneous unicast users/unlimited users using multicast
	Storage Capacity	-
	Alerting	SMTP, UDP, TCP, HTTP
	Pre/Post Alarm	Pre (0,1,2,3,4,5), post (0,1,2,3,4,5,10) sec
	Release for Alarm	Motion detection, I/O or schedule
	BLC	Auto (on/off)
	Electronic Shutter	1/50 (1/60) ~ 1/100,000 sec
	Video Output	1 Vpp, 75 ohm
Min. Illumination	1.0 Lux	
Lens	f = 2.7 ~ 9 mm auto iris lens	
Audio	Audio Communication	2-way audio
	Audio Compression	RTSP: G.711 64 kbps, G.726 32 kbps 3GPP: AMR
	Frequency	300 Hz ~ 3.4 kHz
	Audio In	Connecting base, line in for microphone
	Audio Out	Connecting base, line out for external speaker
Terminal	Network Interface	Ethernet (10 Base-T/100 Base-Tx)
	Video Interface	Connecting base, video composit (NTSC/PAL)
	External Port	Alarm-in x1/relay-out x1
General	Operation Voltage	PoE: 48 V, IEEE 802.3af for option (max. 7 W) LAN: DC 12 V/1 A
	Dimension (W x L x H)/ Weight	136 mm x 136 mm x 106 mm/700 g
	Operation Temperature	0 °C ~ +40 °C, relative moisture 20 % ~ 80 %
	Waterproof	IP66

*Design and specifications are subject to change without prior notice.