

Box, 3 Megapixel 15 fps, H.264/MJPEG/MJPEG, 2-way audio, day/night ICR, SD & SHDC, PoE, ONVIF



- 3 Megapixel multi streaming
- H.264/MPEG4/MJPEG compression
- Advanced motion detection
- 0.2 Lux @ F 1.2; B/W: 0.01 Lux @ F1.2
- 2-way audio
- Built-in SD/SDHL card slot for schedule and alarm recording
- PoE support
- Support 0 °C ~ +50 °C
- ONVIF support

Specification

| | | |
|------------------------|------------------------------|---|
| | Model Name | ISM3411 |
| Video | Camera | 3 Megapixel 15 fps |
| | Image Sensor | 1/2.8" Sony IMX036 CMOS sensor |
| | Effective Pixel | 2048 x 1536 |
| | Minimum Illumination | Color: 0.2 Lux @ F 1.2 B/W: 0.01 Lux @ F 1.2 |
| | Shutter Speed | 1 ~ 1/10000 sec |
| | White Balance | Manual/AWB/ATW |
| | Lens Type | CS/C mount (with adaptor ring), DC iris support (D4 connector) |
| | Operation | Video Compression |
| Video Streaming | | Simultaneous |
| Resolution | | 2048 x 1536/Full HD 1080p/HD 720p/D1/CIF |
| Frame Rate | | Max. 2048 x 1536 (15 fps) |
| Image Setting | | Brightness, contrast, saturation, sharpness, WDR level, privacy masks; Exposure Mode: indoor, outdoor, night, low noise, moving, customize 1 ~ 3, schedule. |
| Audio | | 2-way audio: 1 x input/1 x output (3.5 mm earphone jack); Compression: G.711 u 64 kbps/G.726 32 kbps |
| Alarm | | Recording (SD card, SAMBA, FTP); pre-alarm recording Advanced Motion: 512 zones, Sensitivity: 0 ~ 100 % Trigger: motion detection, schedule, alarm input, ethernet loss, network/remote digital alarm input |
| Network | Event Notification | SD card recording, HTTP, FTP, SMTP, alarm output |
| | Interface | 10/100 Mbps ethernet (RJ-45), Digital I/O: 2 x digital input/2 x digital output/1 x DC output (DC 12 V)/1 x ground, Earphone jack: 2 x 3.5 mm (1 x audio in (mic. in / line in), 1 x audio out). DIP Switch: 1. AES / 2. DC Iris / 3. DHCP / 4. Static IP Reset: Reset for factory default Local Storage Device: SD/SDHC card slot. USB: A-type (2.0) |
| | Protocol | IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, and ONVIF |
| General | Operation Temperature | 0 °C ~ +50 °C (-32 °F ~ 122 °F), Humidity: 10 % ~ 90 %, no condensation |
| | Power Source | DC 12 V/PoE (IEEE 802.3af)/AC 24 V |
| | Regulatory | ONVIF, CE, FCC, RoHS compliant, C-tick |
| | Accessories included | Installation guide, CD x 1 (includes users manual), power adaptor (input AC 100 ~ 240 V, 50/60 Hz, Output: DC 12 V, 1 A), RJ-45 cable x 1 |
| | Dimension | 56 mm x 68 mm x 125 mm |

*Design and specifications are subject to change without prior notice.