

Box, 5 Megapixel 8 fps, H.264, MJPEG4, MJPEG, SD & SHDC, POE, Onvif



- 5 Megapixel multi streaming
- H.264, MPEG4, MJPEG compression
- Motion Detection
- Audio support
- Built-in SD card slot
- PoE support
- Support 0 °C ~ +50 °C
- Onvif support

Specification

Camera	Camera	5 Megapixel 8 fps
	Image Sensor	1/2.5" CMOS sensor
	Effective Pixels	2592 x 1920
	Minimum Illumination	Color: 0.2 Lux @ F 1.2
	Shutter Speed	1 ~ 1/10000 sec
	White Balance	Manual / AWB / ATW
Lens	Lens Type	Auto iris C/CS mount lens
Operation	Video Compression	H.264 / MPEG4 / MJPEG
	Video Streaming	Simultaneous
	Resolution	2592 x 1920 / HD 720p / D1 / CIF
	Frame Rate	Maximum 2592 x 1920 (8 fps)
	Image Setting	Brightness, Contrast, Saturation, Sharpness, White balance, Exposure, AGC, AWB, AES, BLC
	Audio	MPEG4 AAC audio encoding, G.711 audio encoding Built-in high sensitive microphone with 5M maximum audible area. Supports audio mute Support External Speaker for Alarm siren
	Alarm	Motion Detection, 2 D/I & 2 D/O for external sensor and alarm, Alarm siren output (require external speaker)
	Event Notification	FTP, SMTP
Network	Interface	10/100 Mbps Ethernet (RJ-45), RJ-45 Ethernet x 1, Power connection x 1, SD-card slot x 1, Auto Iris Plug x 1, RS-485 x 1, Alarm I/O x 1, Reset Button x 1
	Protocol	IPv4 / v6, TCP / IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, and ONVIF
General	Operation Temperature	0 °C ~ +50 °C (-32 °F~ 122 °F), Humidity: 10 % ~ 90 %, no condensation
	Power Source	DC12 V / PoE (IEEE 802.3af)
	Regulatory	ONVIF, CE, FCC, RoHS compliant, C-Tick
	Accessories included	Installation guide, CD x 1 (includes Users Manual), Power adaptor (Input AC 100~240V, 50/60 Hz, Output: DV12V, 1A)
	Dimension	50 x 70 x 152 mm

*Design and specifications are subject to change without prior notice.