

Indoor dome, 5 Megapixel 8 fps, H.264, MJPEG4, MJPEG, SD & SHDC, POE, Onvif



- 5 Megapixel multi streaming
- H.264, MPEG4, MJPEG compression
- Motion Detection
- Audio support
- Built-in SD card slot
- PoE support
- Support 0 °C ~ +50 °C
- Onvif support

## Specification

<b>Camera</b>	<b>Camera</b>	5 Megapixel 8 fps
	<b>Image Sensor</b>	1/2.5" CMOS sensor
	<b>Effective Pixels</b>	2592 x 1920
	<b>Minimum Illumination</b>	Color: 0.2 Lux @ F 1.2
	<b>Shutter Speed</b>	1 ~ 1/10000 sec
	<b>White Balance</b>	Manual / AWB / ATW
<b>Lens</b>	<b>Lens Type</b>	4.2mm, F1.5
<b>Operation</b>	<b>Video Compression</b>	H.264 / MPEG4 / MJPEG
	<b>Video Streaming</b>	Simultaneous
	<b>Resolution</b>	2592 x 1920 / HD 720p / D1 / CIF
	<b>Frame Rate</b>	Maximum 2592 x 1920 (8 fps)
	<b>Image Setting</b>	Brightness, Contrast, Saturation, Sharpness, White balance, Exposure, AGC, AWB, AES, BLC
	<b>Audio</b>	MPEG4 AAC audio encoding, G.711 audio encoding Built-in high sensitive microphone with 5M maximum audible area. Supports audio mute Support External Speaker for Alarm siren
	<b>Alarm</b>	Motion Detection, 2 D/I & 2 D/O for external sensor and alarm, Alarm siren output (require external speaker)
<b>Network</b>	<b>Event Notification</b>	FTP, SMTP
	<b>Interface</b>	10/100 Mbps Ethernet (RJ-45), RJ-45 Ethernet x 1, Power connection x 1, SD-card slot x 1, Auto Iris Plug x 1, RS-485 x 1, Alarm I/O x 1, Reset Button x 1
<b>General</b>	<b>Protocol</b>	IPv4 / v6, TCP / IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, and ONVIF
	<b>Operation Temperature</b>	0 °C ~ +50 °C (-32 °F~ 122 °F), Humidity: 10 % ~ 90 %, no condensation
	<b>Power Source</b>	DC12 V / PoE (IEEE 802.3af)
	<b>Regulatory</b>	ONVIF, CE, FCC, RoHS compliant, C-Tick
	<b>Accessories included</b>	Installation guide, CD x 1 (includes Users Manual), Power adaptor (Input AC 100~240V, 50/60 Hz, Output: DV12V, 1A)
	<b>Dimension</b>	120 mm x 92 mm

\*Design and specifications are subject to change without prior notice.