

4 ch video server, H.264/MPEG4/JPEG, 2-way audio, SD card support, DC 12 V



- D1 30/25 fps for each channel
- H.264/MPEG-4/JPEG triple streams simultaneously
- 2-way audio
- Mobile view support

Specification

	Model Name	ISS3043
Server	Network Compression	Triple Streams: H.264/MPEG-4/JPEG
	Traffic Control	32/48/64/96/128/196/256/320/384/448/512/576/640/704/768 kbps 1/1.5/2/2.5/3/3.5/4/6/8 Mbps
	Pixels (H x V)	Full D1 (NTSC: 720 x 480/PAL: 720 x 576), CIF, QCIF, 4CIF
	Max. Frame Rate	100 fps (NTSC)/90 fps (PAL)
	Safety	User-ID and password
	Protocol	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP
	Number of User	Max. 10 connections for single video
	Storage Capacity	SD card
	Alerting	SMTP, FTP, HTTP, SD card
	Pre/Post Alarm	Pre (0, 1, 2, 3, 4, 5), post (0, 1, 2, 3, 4, 5, 10) sec
Video	Release for Alarm	Motion detection, I/O or schedule
	Video Input/Output	Video in x 4/looping x 4
Audio	Video Adjustment	Image setting, video streaming setting
	Audio Communication	2-way-halfduplex
	Audio Compression	ADPCM 32 kbps
	Frequency	300 Hz ~ 3.4 kHz
	Audio In	RCA x 4, line in for microphone
Terminal	Audio Out	RCA x 1, line out for external speaker
	Network Interface	Ethernet (10 Base-T/100 Base-Tx), IEEE802.11n/g for option
	Video Interface	Video composited (NTSC/PAL)
	SD Card	SD memory card with the 32 GB, 16 GB, 8 GB, 4 GB ~ 64 MB
General	External Port	Alarm-in x 4/relay-out x 4, RS232, RS485 2 wires
	Operation Voltage	LAN: DC 12 V (max. 7.6 W), WiFi (optional): DC 12 V (max. 8.6 W)
	Dimension (H x W x D)/Weight	44 mm x 218 mm x 202 mm/1,400 g/10 pcs per carton
	Operation Temp.	-10 °C ~ +45 °C, relative moisture 20 % ~ 90 %
	Waterproof	-

*Design and specifications are subject to change without prior notice.

