

Weather proof box camera housing with IP67 standard



- IP67
- Power Input: AC 230 V, AC 24 V, DC 12 V input
- Build in heater
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Pressure die-coast aluminum alloy construction
- PoE optional

Specification

Model Name	CASH132-24	CASH132-D	CASH132-230
Heater Power Input	DC12V or AC 24 V	DC 12 V or AC 24 V	AC 230 V
Camera Power Supported	AV 24 V	AC 24 V or DC 12 V	DC 12 V or AC 230 V
Power Supply	AC 24 V input, 1 × DC 12 V output, 1.5 A	-	-
Heater Control	Dual AC 24 V/DC 12 V heater, main heater switches on at 18 °C & off at 28 °C		AC 230 V mains heater switches on at 18 °C & off at 28 °C
Environmental Operation Temperature	-40 ~ 50 °C		
Temper Glass Thickness	4 mm		
Camera Installation Space (W × H × L)	105 × 80 × 300 mm		
Dimension (W × H × L)	135 × 158 × 450 mm		
Net Weight	2.51 kg		
Weatherproof	IP67		
Certifications	CE, FCC, RoHS		
Installation			

*Design and specifications are subject to change without prior notice.

