

Weather proof box camera housing with IP68 standard



- AC 24 V or AC 90 ~ 240 V
- IR up to 70 m
- Built in heater and blower
- Operation temperature from -40 ~ 50 °C
- IP68
- Vandal proof
- Automatic defogging glass
- Trigger in/out IR control function
- Pressure die-coast aluminum alloy construction

Specification

Model Name	CSAH134-70-AC24V	CSAH134-70-AC90-240V
Power Input	AC 24 V	AC 90 ~ 240 V
Power Consumption	AC 24 V or AC 90 ~ 240 V, 3.5 A	
LED Quality & IR Light Distance	7 IR LEDs, from 50 ~ 70 m	
Infrared Beam Angle	25°, 45° or 25°/45° interlaced	
IR Light On/Off	Photo diode sensor with trigger in / out control	
Heater Control	18 °C (on)/28 °C (off)	
Blower Control	35 °C (on)/25 °C (off)	
Environmental Operation Temperature	-40 ~ 50 °C	
Temper Glass Thickness	4 mm	
Camera Installation Space (W × H × L)	90 × 100 × 250 mm	
Dimension (W × H × L)	160 × 165 × 425 mm	
Net Weight	4140 g	
Weatherproof	IP68	
Certifications	CE, FCC, RoHS	

*Design and specifications are subject to change without prior notice.

