

Weather proof box camera housing with IP66 standard



- IP66
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower (optional)
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in Die Casting Aluminum

## Specification

| Model Name                          | CSAH136                              | CSAH136-H                            | CSAH136-HB                           |
|-------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Type                                | Outdoor side open camera housing     | Outdoor side open camera housing     | Outdoor side open camera housing     |
| Weatherproof                        | IP66                                 | IP66                                 | IP66                                 |
| Material/Color                      | Die-casting Aluminum/Beige           | Die-casting Aluminum/Beige           | Die-casting Aluminum/Beige           |
| Power                               | -                                    | DC 12 V/AC 24 V/AC 110 V/AC 220 V    | DC 12 V/AC 24 V/AC 110 V/AC 220 V    |
| Appearance Size (W x H x L)         | 155 × 110 × 400 mm                   | 155 × 110 × 400 mm                   | 155 × 110 × 400 mm                   |
| View Area (L x W)                   | 58 × 80 mm                           | 58 × 80 mm                           | 58 × 80 mm                           |
| Suitable Camera Size (W x H x L)    | 100 × 70 × 320 mm                    | 100 × 70 × 320 mm                    | 100 × 70 × 320 mm                    |
| Heater Control                      | -                                    | On at 15 °C, off at 25 °C            | On at 15 °C, off at 25 °C            |
| Blower Control                      | -                                    | -                                    | On at 40 °C, off at 30 °C            |
| Environmental Operation Temperature | -                                    | -20 ~ 60 °C                          | -20 ~ 60 °C                          |
| Temper Glass Thickness              | 2 mm                                 | 2 mm                                 | 2 mm                                 |
| Bracket                             | Die casting cable management bracket | Die casting cable management bracket | Die casting cable management bracket |
| Packing                             | 6pcs/cn; 4.2 cuft                    | 6pcs/cn; 4.2 cuft                    | 6pcs/cn; 4.2 cuft                    |
| Unit N.W, G.W.                      | 2.5 kg, 3.2 kg                       | 2.5 kg, 3.2 kg                       | 2.5 kg, 3.2 kg                       |
| Certifications                      | CE, FCC, RoHS                        | CE, FCC, RoHS                        | CE, FCC, RoHS                        |
| IR Wave Length                      | -                                    | -                                    | -                                    |
| IR Distance                         | -                                    | -                                    | -                                    |
| IR H.V. Angle                       | -                                    | -                                    | -                                    |
| IR LEDs                             | -                                    | -                                    | -                                    |
| Expected Lifetime                   | -                                    | -                                    | -                                    |
| IR Light On/Off                     | -                                    | -                                    | -                                    |

\*Design and specifications are subject to change without prior notice.