

PoE weather proof box camera housing with IP66 standard



- DC 12V/1.667 A PoE power support
- Support high-power input and output power up to 20 W
- For PoE and non-PoE cameras
- IP66
- Build in heater/blower (optional)
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in Die Casting Aluminum

Specification

Model Name	CSAH136P	CSAH136P-H	CSAH136P-HB
Type	Outdoor side open camera housing	Outdoor side open camera housing	Outdoor side open camera housing
Weatherproof	IP66	IP66	IP66
Material/Color	Die-casting Aluminum/Beige	Die-casting Aluminum/Beige	Die-casting Aluminum/Beige
DC Output Power	DC 12 V/1.667 A	DC 12 V/1.667 A	DC 12 V/1.667 A
LAN Interface	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)
Appearance Size (W x H x L)	155 × 110 × 400 mm	155 × 110 × 400 mm	155 × 110 × 400 mm
View Area (L x W)	58 × 80 mm	58 × 80 mm	58 × 80 mm
Suitable Camera Size (W x H x L)	100 × 70 × 320 mm	100 × 70 × 320 mm	100 × 70 × 320 mm
Heater Control	-	On at 15 °C, off at 25 °C	On at 15 °C, off at 25 °C
Blower Control	-	-	On at 40 °C, off at 30 °C
Environmental Operation Temperature	-20 ~ 60 °C	-20 ~ 60 °C	-20 ~ 60 °C
Temper Glass Thickness	2 mm	2 mm	2 mm
Bracket	Die casting cable management bracket	Die casting cable management bracket	Die casting cable management bracket
Packing	6pcs/cn; 4.2 cuft	6pcs/cn; 4.2 cuft	6pcs/cn; 4.2 cuft
Unit N.W, G.W.	2.5 kg, 3.2 kg	2.5 kg, 3.2 kg	2.5 kg, 3.2 kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-	-
IR Distance	-	-	-
IR H.V. Angle	-	-	-
IR LEDs	-	-	-
Expected Lifetime	-	-	-
IR Light On/Off	-	-	-

*Design and specifications are subject to change without prior notice.