

Weather proof box camera housing with IP66 standard and IR 70 m



- IP66
- Power Input: DC 12 V input (optional adaptor required for AC 230 V, AC 110 V/AC 24 V)
- Build in heater/blower/sunshield
- IR 50 ~ 70 m
- Operation Temperature: -20 °C ~ 50 °C (double heater for -40 °C ~ 50 °C)
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- IR synchronization (auto control IR on while less than 3 Lux)
- Made in die-casting Aluminum

Specification

Model Name	CASH136-HB
Type	Outdoor back open camera housing
Weatherproof	IP66
Material/Color	Top: ABS & PC/bottom & sunshield: Die-casting Aluminum
Power	DC 12 V (optional adaptor required for AC 24 V, AC 120 V, AC 220 V)
Appearance Size (W × H × L)	157 × 130 × 460 mm
View Area (L × W)	75 × 85 mm
Suitable Camera Size (W × H × L)	108 × 75 × 300 mm
Heater Control	On at 15 °C, off at 25 °C
Blower Control	On at 40 °C, off at 30 °C
Environmental Operation Temperature	-20 °C ~ 60 °C (double heater for -40 °C ~ 60 °C)
Temper Glass Thickness	3 mm
Bracket	Die casting cable management bracket
Packing	6 pcs/cn, 5.1 cuft
Unit N.W, G.W.	3.2 kg, 3.7 kg
Certifications	CE, FCC, RoHS
IR Wave Length	850 nm
IR Distance	50 m ~ 70 m
IR H.V. Angle	30°
IR LEDs	8 mm LED 28 units
Expected Lifetime	More than 25000 hr
IR Light On/Off	Auto control (less than 3 Lux on)

*Design and specifications are subject to change without prior notice.

