

# CSAH140

Die-Casting Products

Accessory - Box Camera Housings

Weather proof side open box camera housing with IP68 standard



- IP68 rating
- Designed for indoor and outdoor applications
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in die casting Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions
- Bundled cable-management bracket

## Specification

Model	CSAH140	CSAH140-HB
Type	Outdoor side open	Outdoor side open
Weatherproof	IP68	IP68
Material/Color	Die-casting Aluminum/Beige and white epoxy powder coating	Die-casting Aluminum/Beige and white epoxy powder coating
Power	-	DC 12 V/AC 24 V/AC 110 V/AC 220 V
Appearance Size (W × H × L)	145 × 109 × 406 mm	145 × 109 × 406 mm
View Area (L × W)	92 × 76 mm	92 × 76 mm
Suitable Camera Size (W × H × L)	100 × 65 × 220 mm	100 × 65 × 220 mm
Heater Control	-	On at 15 °C, off at 25 °C
Blower Control	-	On at 40 °C, off at 30 °C
Environmental Operation Temperature	-	-50 ~ 50 °C
Temper Glass Thickness	2 mm	2 mm
Bracket	Die casting cable management bracket	Die casting cable management bracket
Packing	6 pcs/cn, 4.3 cuft	6 pcs/cn, 4.3 cuft
Unit N.W, G.W.	2.8 kg, 3.5 kg	3 kg, 3.7 kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-
IR Distance	-	-
IR H.V. Angle	-	-
IR LEDs	-	-
Expected Lifetime	-	-
IR Light On/Off	-	-



\*Design and specifications are subject to change without prior notice.