

CSAH140P

Die-Casting Products

Accessory - PoE Box Camera Housings

PoE weather proof side open box camera housing with IP68 standard



- DC 12 V/1.667 A PoE power support
- Support high-power input and output power up to 20 W
- For PoE and non-PoE cameras
- IP68 rating
- Designed for indoor and outdoor applications
- Build in heater/blower
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in die casting Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions
- Bundled cable-management bracket

Specification

Model	CSAH140P	CSAH140P-HB
Type	Outdoor side open	Outdoor side open
Weatherproof	IP68	IP68
Material/Color	Die-casting Aluminum/Beige and white epoxy powder coating	Die-casting Aluminum/Beige and white epoxy powder coating
DC Output Power	DC 12 V/1.667 A	DC 12 V/1.667 A
LAN Interface	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)
Appearance Size (W × H × L)	145 × 109 × 406 mm	145 × 109 × 406 mm
View Area (L × W)	92 × 76 mm	92 × 76 mm
Suitable Camera Size (W × H × L)	100 × 65 × 220 mm	100 × 65 × 220 mm
Heater Control	-	On at 15 °C, off at 25 °C
Blower Control	-	On at 40 °C, off at 30 °C
Environmental Operation Temperature	-25 ~ 50 °C	-25 ~ 50 °C
Temper Glass Thickness	2 mm	2 mm
Bracket	Die casting cable management bracket	Die casting cable management bracket
Packing	6 pcs/cn, 4.3 cuft	6 pcs/cn, 4.3 cuft
Unit N.W, G.W.	2.8 kg, 3.5 kg	3 kg, 3.7 kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-
IR Distance	-	-
IR H.V. Angle	-	-
IR LEDs	-	-
Expected Lifetime	-	-
IR Light On/Off	-	-



*Design and specifications are subject to change without prior notice.