

# CSAH141

Die-Casting Products

Accessory - IR Housing

Weather proof side open box camera housing with IP68 standard and IR 80 m



- IP68 rating
- Designed for indoor and outdoor applications
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower/IR (80 m)
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in die casting Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions
- Bundled cable-management bracket

## Specification

<b>Model</b>	<b>CSAH141</b>
<b>Type</b>	Outdoor side open
<b>Weatherproof</b>	IP68
<b>Material/Color</b>	Die-casting Aluminum/Beige and white epoxy powder coating
<b>Power</b>	DC 12 V/AC 24 V/AC 110 V/AC 220 V
<b>Appearance Size (W × H × L)</b>	145 × 109 × 406 mm
<b>View Area (L × W)</b>	92 × 76 mm
<b>Suitable Camera Size (W × H × L)</b>	100 × 65 × 220 mm
<b>Heater Control</b>	On at 15 °C, off at 25 °C
<b>Blower Control</b>	On at 40 °C, off at 30 °C
<b>Environmental Operation Temperature</b>	-50 ~ 50 °C
<b>Temper Glass Thickness</b>	2 mm, dual glasses
<b>Bracket</b>	Die casting cable management bracket
<b>Packing</b>	6 pcs/cn, 4.3 cuft
<b>Unit N.W, G.W.</b>	3 kg, 3.7 kg
<b>Certifications</b>	CE, FCC, RoHS
<b>IR Wave Length</b>	850 nm
<b>IR Distance</b>	80 m
<b>IR H.V. Angle</b>	30°
<b>IR LEDs</b>	6 pcs, IR on when lux is lower than 4 Lux
<b>Expected Lifetime</b>	20,000 hr
<b>IR Light On/Off</b>	-



\*Design and specifications are subject to change without prior notice.