

CSAH142P

Die-Casting Products

Accessory - PoE Box Camera Housings

PoE weather proof side open box camera housing with IP67 standard



- DC 12V/1.667 A PoE power support
- Support high-power input and output power up to 20 W
- For PoE and non-PoE cameras
- IP67 rating
- Designed for indoor and outdoor applications
- Build in heater/blower
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in extruded Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions

Specification

Model	CSAH142P	CSAH142P-HB
Type	Outdoor side open	Outdoor side open
Weatherproof	IP67	IP67
Material/Color	Extruded Aluminum/Beige and white epoxy powder coating	Extruded Aluminum/Beige and white epoxy powder coating
DC Output Power	DC 12 V/1.667 A	DC 12 V/1.667 A
LAN Interface	RJ-45 × 2 (PoE in/data output)	RJ-45 × 2 (PoE in/data output)
Appearance Size (W × H × L)	147 × 115 × 377 mm	147 × 115 × 377 mm
View Area (L × W)	75 × 75 mm	75 × 75 mm
Suitable Camera Size (W × H × L)	95 × 70 × 227 mm	95 × 70 × 227 mm
Heater Control	-	On at 15 °C, off at 25 °C
Blower Control	-	On at 40 °C, off at 30 °C
Environmental Operation Temperature	-25 ~ 50 °C	-25 ~ 50 °C
Temper Glass Thickness	2 mm	2 mm
Bracket	Die casting standard bracket	Die casting standard bracket
Packing	12 pcs/cn, 3.1 cuft	12 pcs/cn, 3.1 cuft
Unit N.W, G.W.	1.25 kg, 1.8 kg	1.25 kg, 1.8 kg
Certifications	CE, FCC, RoHS	CE, FCC, RoHS
IR Wave Length	-	-
IR Distance	-	-
IR H.V. Angle	-	-
IR LEDs	-	-
Expected Lifetime	-	-
IR Light On/Off	-	-



*Design and specifications are subject to change without prior notice.