

Weather proof side open box camera housing with IP66 standard and 40 m IR



- IP66 rating
- Designed for indoor and outdoor applications
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower
- IR 40 m
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in extruded Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions

Specification

Model	CSAH143
Type	Outdoor side open
Weatherproof	IP66
Material/Color	Extruded Aluminum/Beige and white epoxy powder coating
Power	AC 230 V, AC 110 V/AC 24 V/DC 12 V input
Appearance Size (W × H × L)	147 × 115 × 320 mm
View Area (L × W)	75 × 75 mm
Suitable Camera Size (W × H × L)	95 × 70 × 177 mm
Heater Control	-
Blower Control	-
Environmental Operation Temperature	-20 ~ 50 °C
Temper Glass Thickness	2 mm, dual glasses
Bracket	Die casting cable management bracket
Packing	12 pcs/cn, 3.1 cuft
Unit N.W, G.W.	1.25 kg, 1.8 kg
Certifications	CE, FCC, RoHS
IR Wave Length	850 nm
IR Distance	40 m
IR H.V. Angle	30°
IR LEDs	42 pcs, 8 Ø LED
Expected Lifetime	More than 25000 hr
IR Light On/Off	-



*Design and specifications are subject to change without prior notice.