

# CSAH144

Die-Casting Products

Accessory - IR Box Camera Housings

Weather proof side open box camera housing with IP66 standard and 50 ~ 70 m IR



- IP66 rating
- Designed for indoor and outdoor applications
- Power Input: AC 230 V, AC 110 V/AC 24 V/DC 12 V input
- Build in heater/blower
- IR 50 ~ 70 m
- Adjustable sliding camera tray & sealed cable entry glands
- Fully-cable management system with swivel bracket
- Made in extruded Aluminum
- Lightweight for easy wall mounting
- High impact resistance
- Side opening
- Easy access for service and installation
- Withstand severe environment conditions

## Specification

<b>Model</b>	<b>CSAH144</b>
<b>Type</b>	Outdoor side open
<b>Weatherproof</b>	IP66
<b>Material/Color</b>	Extruded Aluminum/Beige and white epoxy powder coating
<b>Power</b>	AC 230 V, AC 110 V/AC 24 V/DC 12 V input
<b>Appearance Size (W × H × L)</b>	147 × 115 × 320 mm
<b>View Area (L × W)</b>	75 × 75 mm
<b>Suitable Camera Size (W × H × L)</b>	95 × 70 × 177 mm
<b>Heater Control</b>	-
<b>Blower Control</b>	-
<b>Environmental Operation Temperature</b>	-20 ~ 50 °C
<b>Temper Glass Thickness</b>	2 mm, dual glasses
<b>Bracket</b>	Die casting cable management bracket
<b>Packing</b>	12 pcs/cn, 3.1 cuft
<b>Unit N.W, G.W.</b>	1.25 kg, 1.8 kg
<b>Certifications</b>	CE, FCC, RoHS
<b>IR Wave Length</b>	850 nm
<b>IR Distance</b>	50 ~ 70 m
<b>IR H.V. Angle</b>	30°
<b>IR LEDs</b>	42 pcs, 8 Ø LED
<b>Expected Lifetime</b>	More than 25000 hr
<b>IR Light On/Off</b>	-

\*Design and specifications are subject to change without prior notice.

