

IP66 PTZ position system with infrared and 16 preset position for HD lens & IP cameras



- Outdoor integration without exposed line design
- Support many kinds of LED lamps (infrared 850 nm/940nm or white)
- 360° horizontal rotation at up to 18°/sec
- 105° vertical rotation at up to 18°/sec
- Wiper function
- 16 preset positions
- Auto pan function
- Protection grade IP66
- Video/power/RS485 lightning protection
- AC 110 V/AC 220 V/AC 24 V power input

Specification

Model	PS001-I
Infrared Distance	-
Camera	Install HD lens / With IP cameras
Communication	RS485/ethernet-based control
Preset Position	16
Pan Range	360° endless
Pan Speed	18°/sec
Tilt Range	-50 ~ 45°
Tilt Speed	18°/sec
Wiper Function	Yes
Communication Interface Protection	Yes
Power protection	Yes
IP Grade	IP66
Weight	10 kg
Dimension (W × L × H)	480 × 135 × 450.5 mm
Power Supply	AC 110 V/AC 220 V/AC 24 V
Power Consumption	36 W (when heater is on)
Operation Temperature	-30 °C ~ 50 °C
The Maximum Size of the Lens and Camera Combination (W × H × L)	270 × 87 × 80 mm

*Design and specifications are subject to change without prior notice.