

**IP66 PTZ position system with infrared and 16 preset position for HD lens & IP cameras**



- Outdoor integration without exposed line design
- Support many kinds of LED lamps (infrared 850 nm/940 nm or white)
- 360° horizontal rotation at up to 18°/sec
- 105° vertical rotation at up to 18°/sec
- Wiper function
- 16 preset positions
- Auto pan function
- Protection grade IP66
- Video/power/RS485 lightning protection
- IR 100 m/150 m

## Specification

<b>Model</b>	PS002-150IR	PS002-100IR
<b>Infrared Distance</b>	150 m (850 nm)	100 m (850 nm)
<b>Camera</b>	Install HD lens / With IP cameras	Install HD lens / With IP cameras
<b>Communication</b>	RS485/ethernet-based control	RS485/ethernet-based control
<b>Preset Position</b>	16	16
<b>Pan Range</b>	360° endless	360° endless
<b>Pan Speed</b>	18°/sec	18°/sec
<b>Tilt Range</b>	-50 ~ 45°	-50 ~ 45°
<b>Tilt Speed</b>	18°/sec	18°/sec
<b>Wiper Function</b>	Yes	Yes
<b>Communication Interface Protection</b>	Yes	Yes
<b>Power protection</b>	Yes	Yes
<b>IP Grade</b>	IP66	IP66
<b>Weight</b>	11 kg	11 kg
<b>Dimension (W × L × H)</b>	480 × 395 × 450.5 mm	481 × 395 × 450.5 mm
<b>Power Supply</b>	AC 110 V/AC 220 V/AC 24 V	AC 110 V/AC 220 V/AC 24 V
<b>Power Consumption</b>	36 W (when heater is on)	36 W (when heater is on)
<b>Operation Temperature</b>	-30 °C ~ 50 °C	-30 °C ~ 50 °C
<b>The Maximum Size of the Lens and Camera Combination (W × H × L)</b>	270 × 87 × 80 mm	270 × 87 × 80 mm

\*Design and specifications are subject to change without prior notice.