

IP66 PTZ position system with infrared and 128 preset position for zoom camera



- Outdoor integration without exposed line design
- Support many kinds of LED lamps (infrared 850 nm/940 nm or white)
- 360° horizontal rotation at up to 80°/sec
- 180° vertical rotation at up to 60°/sec
- 128 preset positions & 2 tours
- Automatic homing function
- Long-focus speed limit function(AU-M7A)
- Off memory
- Protection grade IP66
- IR 100 m/150 m

## Specification

Model	PS005-150MR	PS005-100MR
Infrared Distance	150 m (850 nm)	100 m (850 nm)
Camera	Install camera module	Install camera module
Communication	RS485	RS485
Preset Position	128	128
Pan Range	360° endless	360° endless
Pan Speed	0.5 ~ 80°/sec	0.5 ~ 80°/sec
Tilt Range	-90 ~ 90°	-90 ~ 90°
Tilt Speed	0.5°—60°/sec	0.5°—60°/sec
Wiper Function	No	No
Communication Interface Protection	Yes	Yes
Power protection	Yes	Yes
IP Grade	IP66	IP66
Weight	6 kg	6 kg
Dimension (W × L × H)	320 × 200 × 380 mm	320 × 200 × 380 mm
Power Supply	AC 24 V	AC 24 V
Power Consumption	55 W (when heater is on)	55 W (when heater is on)
Operation Temperature	-35 °C ~ 50 °C	-35 °C ~ 50 °C

\*Design and specifications are subject to change without prior notice.