

*IP66 PTZ position system with infrared and 128 preset position for zoom camera*



- Outdoor integration without exposed line design
- Support many kinds of LED lamps (infrared 850 nm/940 nm or white)
- 360° horizontal rotation at up to 80°/sec
- 180° vertical rotation at up to 60°/sec
- 128 preset positions & 2 tours
- Automatic homing function
- Long-focus speed limit function
- Off memory
- Protection grade IP66
- Video/power/RS485 lightning protection

## Specification

Model	PS006-150ZR	PS006-100ZR
<b>Infrared Distance</b>	150 m (850 nm)	100 m (850 nm)
<b>Camera</b>	Install zoom camera	Install zoom camera
<b>Communication</b>	RS485	RS485
<b>Preset Position</b>	128	128
<b>Pan Range</b>	360° endless	360° endless
<b>Pan Speed</b>	0.5 ~ 80°/sec	0.5 ~ 80°/sec
<b>Tilt Range</b>	-90 ~ 90°	-90 ~ 90°
<b>Tilt Speed</b>	0.5°—60°/sec	0.5°—60°/sec
<b>Wiper Function</b>	No	No
<b>Communication Interface Protection</b>	Yes	Yes
<b>Power protection</b>	Yes	Yes
<b>IP Grade</b>	IP66	IP66
<b>Weight</b>	6 kg	6 kg
<b>Dimension (W × L × H)</b>	320 × 200 × 380 mm	320 × 200 × 380 mm
<b>Power Supply</b>	AC 24 V	AC 24 V
<b>Power Consumption</b>	55 W (when heater is on)	55 W (when heater is on)
<b>Operation Temperature</b>	-35 °C ~ 50 °C	-35 °C ~ 50 °C

\*Design and specifications are subject to change without prior notice.