



Home Surveillance

http://www.tsict.com



TSHB4101

IP66 IR Vandal Proof Wireless Camera with 7-inch LCD Surveillance Monitor

IP66 IR vandal proof wireless camera with 7-inch LCD surveillance monitor



Model	TSHB4101
× H)	
Weight	0.33 kg (0.73 lb)
Power	DC 9 V, 500 mA
Operating	-10 °C to 50 °C (14 °F to 122 °F)
Temperature	
Monitor	
Frequency	2.4 GHz
Antenna	Monopole Antenna
LCD Screen Size	7-inch
Number of Color	Full color
Motion Alarm	Yes
Dimensions (W × L	208 mm × 27 mm × 125 mm (8.19 in × 1.06 in × 4.92 in)
× H)	
Weight	0.4 kg (0.88 lb)
Power	6 V DC, 800 mA, Li-ion battery
Operating	0 °C to 40 °C (32 °F to 104 °F)
Temperature	

*Design and specifications are subject to change without prior notice.

Features

- IP66 level weather and vandal proof metal camera
- Intensive 10 m (32.8 ft) night vision
- Clear VGA quality and audio streaming from camera to minitor
- Real time quad view for 4 cameras monitoring simultaneously
- Digital wireless technology ensures zero interference and 100 % privacy
- Record clear VGA quality video and audio on SD card (maximum 32 GB)
- Motion activation alarm
- Schedule recording
- Monitor can connect with PC via USB and stream video to PC
- Plug and play
- Monitor has backup lithium-ion battery
- Extended 300 m (984 ft) transmission distance
- Wifi friendly wireless technology to coexist with Wifi network

Tech Specs

Model	TSHB4101
Camera	
Frequency	2.4 GHz
Antenna	Dipole Antenna
Transmission	300 m (984 ft) (line of sight)
Distance	
Modulation	GFSK, FHSS
Image Sensor	Color CMOS
Effective Pixels (H ×	640 × 480 pixels
V)	
Lens	f = 3.6 mm, F2.2
IR LED	20 pieces
Dimensionss (W × L	65 mm × 170 mm × 90 mm (2.56 in × 6.69 in × 3.54 in)

TSict (Tailored Solution international co., ltd.) E-mail: sales@tsict.com, <u>http://www.tsict.com</u> © Copyright 2013, TSict (Tailored Solution international co., ltd.). All Rights Reserved.



TSHB4102

Wireless Camera with 7-inch LCD Surveillance Monitor

Wireless camera with 7-inch LCD surveillance monitor



Model	TSHB4102
Weight	209 g (0.44 lb)
Dimensions (W × L	100 mm × 158 mm × 90 mm (3.94 in × 6.22 mm × 3.54
× H)	in)
Power	6 V DC, 800 mA, 4 × AAA batteries
Operating	0 °C to 40 °C (32 °F to 104 °F)
Temperature	
Monitor	
Frequency	2.4 GHz
Antenna	Monopole Antenna
LCD Screen Size	7-inch
Number of Color	Full color
Motion Alarm	Yes
Dimensions (W × L	208 mm × 27 mm × 125 mm (8.19 in × 1.06 in × 4.92 in)
× H)	
Weight	404 g (0.88 lb)
Power	6 V DC, 800 mA, Li-ion battery
Operating	0 °C to 40 °C (32 °F to 104 °F)
Temperature	

*Design and specifications are subject to change without prior notice.

Features

- Split screen view when Parent unit is hooked up with multiple Bay units
- · Movement detection informs parents when baby awake without crying
- · Digital Pan-Tilt Zoom gives the best view of baby video
- Display baby room's temperature on monitor and alert parents once room temperature is out of comfort zone
- Intelligent design for baby monitor co-existence with Wifi networks at home
- Parent plays lullaby to soothe baby from Parent unit
- Talk back function allows parents to talk to baby from parent units
- Digital wireless technology ensures zero interference and 100 % privacy
- See baby clearly on 7-inch LCD with VGA quality video streaming
- · Parent unit comes with Lithium lon battery for convenient porability
- Battery level and signal strength information is displayed on parent unit screen

Tech Specs

Model	TSHB4102
Camera	
Frequency	2.4 GHz
Antenna	Dipole Antenna
Transmission	150 m (492 ft) (line of sight)
Distance	
Modulation	GFSK, FHSS
Image Sensor	Color CMOS
Effective Pixels (H ×	640 × 480 pixels
V)	
Lens	f = 3.0 mm, F2.4
IR LED	-



TSHB4103

Wireless Camera with 2.36-inch LCD Surveillance Monitor

Wireless camera with 2.36-inch LCD surveillance monitor



Model	TSHB4103
Temperature	
Monitor	
Frequency	2.4 GHz
Antenna	Monopole Antenna
LCD Screen Size	2.36-inch TFT
Number of Color	Full color
Motion Alarm	No
Weight	0.35 kg (0.77 lb)
Dimensions (W × L	156 mm × 27 mm × 105 mm (6.14 in × 1.06 in × 4.13 in)
× H)	
Power	6 V DC, 800 mA, Li-ion battery
Operating	0 °C to 40 °C (32 °F to 104 °F)
Temperature	

*Design and specifications are subject to change without prior notice.

Features

- Digital wireless technology provides interference free and 100 % privacy
- Longer distance than traditional analogue video baby monitor
- Automatic night vision activation on camera
- Sound level light indicator
- 2.36-inch LCD panel
- Monitor comes up with built in Li battery charger
- Control lable Brightness/Volume
- Auto Exposure/White-Balance
- · Lullabies to soothe baby

Tech Specs

Model	TSHB4103
Camera	
Frequency	2.4 GHz to 2.483 GHz
Antenna	Dipole Antenna
Transmission	150 m (492 ft) (line of sight)
Distance	
Modulation	FSK, FHSS
Image Sensor	Color CMOS
Effective Pixels (H ×	640 × 480 pixels
V)	
Lens	f = 3.0 mm, F2.4
IR LED	-
Weight	0.22 kg (0.49 lb)
Dimensions (W × L	$120 \text{ mm} \times 172 \text{ mm} \times 90 \text{ mm} (4.72 \text{ in} \times 6.77 \text{ in} \times 3.54 \text{ in})$
× H)	
Power	6 V DC, 800 mA, 4 × AAA batteries
Operating	0 °C to 40 °C (32 °F to 104 °F)